



**CERTIFIED FOR:**

**JOB NAME** \_\_\_\_\_

**LOCATION** \_\_\_\_\_

**CUSTOMER** \_\_\_\_\_

**CUSTOMER P.O.** \_\_\_\_\_

**Submittal Information: MPH-24D:24/9 Pedestal Hydrant**

**Composition:**



- Black powder coated cast aluminum Weather-Guard Dome Handle
- Grade 304 stainless steel shroud w/ welded stainless steel flange
- Male Hose Fitting / Vacuum Breaker

**Mounting Hardware**

- Black powder coated under-deck support flange w/ hardware

**Features:**

- The Auto-Drain port will discharge the water remaining in the standpipe to an open-site drain.
- The Hydrant utilizes a bronze full port auto drain ball valve within the stainless steel shroud.
- The Under-deck Flange prevents the Hydrant from becoming dislodged from the roof membrane during operation.
- The Weather-Guard Domed Handle prevents moisture from entering the assembly when the valve is in the OFF position.
- Provided with "loose fit" wye strainer for field installation.

**Options:**

Deck Cap – Suffix "D"

Suffix: xx/yy – Extended shroud for above or below roofline – 6" increments

**Practical Application**

Where there is concern for potential damage to the hydrant assembly due to severe cold weather, the MPH-24D:24/9 Pedestal Hydrant with its Weather-Guard Dome provides a freeze proof hose station at required locations. The Auto-Drain port is located below the freeze line at the base of the hydrant. The Stainless Steel Shroud and Base allow the contractor to make a positive, weather tight flashing to the hydrant in rooftop applications.

**Warranty:**

ISIMET/MAPA,LLC will repair or replace any defective parts or workmanship of this product for a period of one year from date of delivery. Damage caused by incorrect installation, alteration or improper usage is not warranted. Recovery rights shall be limited to the total sum of the amounts paid for the product by the purchaser.

**Limits of Liability:**

ISIMET/MAPA,LLC 's liability shall be limited to costs of repair or replacement parts. Hydrants are not intended for usage other than those expressly described in this document. ISIMET/MAPA,LLC shall not be liable for damage or injury caused by the improper use of the product.

**CERTIFICATION DATA**

QUANTITY	Style		Deck Cap	Dimensions <i>(If other than Standard 24" above roofline)</i>	Notes
	Roof/Yard				
	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>		
	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>		
	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>		
	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>		

<b>DRAWN</b>	<b>CHECKED</b>	<b>DATE</b>	<b>DWG.NO.</b>
--------------	----------------	-------------	----------------

OP2008-MPH24D